



TEKSAN DIESEL GENERATING SET

(230/400 V 50 Hz - 1500 rpm)

GEN-SET MODEL

TJ200CM

GEN-SET POWER RATING

*Stand-by Power

kVA

203

**Prime Power

kVA

184

* Stand-by power 100% is applicable for supplying emergency power for the duration of the utility power outage, no overload permissible. A stand-by rated Genset should be sized for a maximum of an 80 % average load factor and 200 hrs of operation per year

** Prime power is available for an unlimited number of hours per year in a variable load application. Variable load should exceed a 70 % average of the prime power during any operating of 250 hours , total operating time at 100 % prime power shall not exceed 500 hours per year

DIMENSIONS W x L x H

Open Skid

mm

1000x2800x1490

Canopied

mm

1000x4000x1950

FUEL TANK CAPACITY

Open Skid

lt

290

Canopied

lt

416

WEIGHT

Open Skid

kg

1600

Canopied

kg

2240

ENGINE

Manufacturer

CUMMINS

Origin

UK

Model

6CTA8.3-G2

Governor Type

Mechanical

Speed

rpm

1500

Net Stand-by Power

kWm

175

Net Prime Power

kWm

158

Cylinder number and config.

In line-6

Bore/Stroke

mm

114x135

Displacement

lt

8,3

Compression ratio

16,8

Aspiration

Turbocharged
&
aftercooled

Cooling

Water Cooled

Electrical system

V

24

Fuel Consumption

% 100 load

lt/h

40

% 75 load

lt/h

30

% 50 load

lt/h

20

Lub.Oil Capacity

lt

23,8

Coolant Capacity with radiator

lt

35

ALTERNATOR

Manufacturer

MARELLI

Origin

ITALY

Model

MJB250MB4

Stand By Power

kVA

205

Power Factor

0,8

Efficiency

%

93,0

Number of Bearing

Single

Leads Number

12

Voltage

V

230/400

Voltage Regulation Accuracy

±1%

Frequence

Hz

50

Insulation Class

H

Protection

IP23

Excitation System

Brushless, AVR

Connection

Star

All information given in this leaflet is intended for general purposes only. Due to a policy of continuous improvement, Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's curr