



## TEKSAN DIESEL GENERATING SET

(230/400 V 50 Hz - 1500 rpm)

### GEN-SET MODEL

TJ2260CM

### GEN-SET POWER RATING

*Stand-by Power	kVA	2261
**Prime Power	kVA	2038

\* Stand-by power 100% is applicable for supplying emergency power for the duration of the utility power outage, no overload permissible. A stand-by rated Genset should be sized for a maximum of an 80 % average load factor and 200 hrs of operation per year

\*\* Prime power is available for an unlimited number of hours per year in a variable load application. Variable load should exceed a 70 % average of the prime power during any operating of 250 hours , total operating time at 100 % prime power shall not exceed 500 hours per year

### DIMENSIONS W x L x H

Open Skid	mm	2000x6320x2610
Canopied	mm	TBA

### FUEL TANK CAPACITY

Open Skid	lt	3500
Canopied	lt	3500

### WEIGHT

Open Skid	kg	16650
Canopied	kg	TBA

### ENGINE

Manufacturer		CUMMINS
Origin		UK
Model		QSK60-G4
Governor Type		Electronic/A1
Speed	rpm	1500
Net Stand-by Power	kWm	1880
Net Prime Power	kWm	1695
Cylinder number and config.		V-16
Bore/Stroke	mm	159x190
Displacement	lt	60.2
Compression ratio		14.5
Aspiration		Turbocharged & aftercooled
Cooling		Water Cooled
Electrical system	V	24
Fuel Consumption		
% 100 load	lt/h	400
% 75 load	lt/h	307
% 50 load	lt/h	217
Lub.Oil Capacity	lt	280
Coolant Capacity with radiator	lt	451

### ALTERNATOR

Manufacturer		MARELLI
Origin		ITALY
Model		MJB500MB4
Stand By Power	kVA	2370
Power Factor		0.8
Efficiency	%	96.2
Number of Bearing		Single
Leads Number		6
Voltage	V	230/400
Voltage Regulation Accuracy		±1%
Frequence	Hz	50
Insulation Class		H
Protection		IP23
Excitation System		Brushless, AVR
Connection		Star

All information given in this leaflet is intended for general purposes only. Due to a policy of continuous improvement, Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's curr