



TEKSAN DIESEL GENERATING SET

230/400 V 50 Hz - 3000 rpm

GEN-SET MODEL**TJ10MS**

GEN-SET POWER RATING

*Stand-by Power	kVA	10
**Prime Power	kVA	8

* Standby Power available a variable load in the event of a main power network failure. No overload is permitted.

** Prime Power available at variable load in lieu of main power network. An overload of 10% is permitted for one hour in every twelve hours of operation.

DIMENSIONS W x L x H

Open Skid	mm	700x1300x870
Canopied	mm	700x2000x1050

FUEL TANK CAPACITY

Open Skid	lt	39
Canopied	lt	39

WEIGHT

Open Skid	kg	490
Canopied	kg	580

ENGINE

Manufacturer		MITSUBISHI
Origin		JAPAN
Model		L2E 61SDH
Governor Type		Mechanical
Speed		3000
Net Stand-by Power	kWm	9,5
Net Prime Power	kWm	8,1
Cylinder number and config.		In line - 2
Bore/Stroke	mm	76 x 70
Displacement	lt	0,635
Compression ratio		23
Aspiration		Naturally aspirated
Cooling		Water Cooled
Electrical system	V	12
Fuel Consumption at full load	lt/h	2,6
Lub.Oil Capacity	lt	2,4
Coolant Capacity with radiator	lt	2,75

ALTERNATOR

Manufacturer		SINCRO
Origin		ITALY
Model		ET2 LBR
Stand By Power	kVA	11
Power Factor		0,8
Efficiency	%	83,0
Number of Bearing		Single
Voltage	V	230/400
Voltage Regulation Accuracy		±2%
Frequence	Hz	50
Insulation Class		H
Protection		IP21
Excitation System		Brushless, AVR

All ratings data based on operation under ISO 3046 conditions using typical fan sizes and drive ratios. For operation outside of these conditions please consult to Teksan.

All information given in this leaflet is intended for general purposes only. Due to a policy of continuous improvement, Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current conditions of sales.