



## TEKSAN DIESEL GENERATING SET

(230/400 V 50 Hz - 1500 rpm)

GEN-SET MODEL

TJ655PE

### GEN-SET POWER RATING

*Stand-by Power	kVA	655
**Prime Power	kVA	562

\*Stand-by Power is limited to 500 hours annual usage with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of the annual usage may be run continuously. No overload is permitted on standby power

\*\*Prime power is an unlimited hours usage with an average load factor 80% of the published prime power rating over each 24 hour period. A 10% overload is available for one hour in every twelve hour operation

### DIMENSIONS W x L x H

Open Skid	mm	1300x3700x2074
Canopied	mm	1650x5000x2250

### FUEL TANK CAPACITY

Open Skid	lt	885
Canopied	lt	984

### WEIGHT

Open Skid	kg	4400
Canopied	kg	5350

### ENGINE

Manufacturer		PERKINS
Origin		UK
Model		2806C-E18TAG1A
Governor Type		Electronic
Speed	rpm	1500
Net Stand-by Power	kWm	553
Net Prime Power	kWm	475
Cylinder number and config.		In line - 6
Bore/Stroke	mm	145/183
Displacement	lt	18,10
Compression ratio		14,5
Aspiration		Turbocharged & aftercooled
Cooling		Water Cooled
Electrical system	V	24
Fuel Consumption		
% 100 load	lt/h	108,0
% 75 load	lt/h	81,0
% 50 load	lt/h	56,0
Lub.Oil Capacity	lt	55,5
Coolant Capacity with radiator	lt	61,0

### ALTERNATOR

Manufacturer		MARELLI
Origin		ITALY
Model		MJB355MA4
Stand By Power	kVA	750
Power Factor		0,8
Efficiency	%	94,7
Number of Bearing		Single
Leads Number		12
Voltage	V	230/400
Voltage Regulation Accuracy		±1%
Frequency	Hz	50
Insulation Class		H
Protection		IP23
Excitation System		Brushless, AVR
Connection		Star

All information given in this leaflet is intended for general purposes only. Due to a policy of continuous improvement, Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current