



TEKSAN DIESEL GENERATING SET
(230/400 V 50 Hz - 1500 rpm)

GEN-SET MODEL

TJ160PR

GEN-SET POWER RATING

*Stand-by Power	kVA	156
**Prime Power	kVA	141

*Stand-by Power is limited to 500 hours annual usage with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of the annual usage may be run continuously. No overload is permitted on standby power

**Prime power is an unlimited hours usage with an average load factor 80% of the published prime power rating over each 24 hour period. A 10% overload is available for one hour in every twelve hour operation

DIMENSIONS W x L x H

Open Skid	mm	750x2400x1475
Canopied	mm	1000x3250x1700

FUEL TANK CAPACITY

Open Skid	lt	139
Canopied	lt	168

WEIGHT

Open Skid	kg	1440
Canopied	kg	1860

ENGINE

Manufacturer		PERKINS
Model		1006TAG
Governor Type		Electronic
Speed	rpm	1500
Net Stand-by Power	kWm	134,0
Net Prime Power	kWm	121,0
Cylinder number and config.		In line - 6
Bore/Stroke	mm	100/127
Displacement	lt	5,99
Compression ratio		17

Aspiration Turbocharged
&
aftercooled

Cooling Water Cooled

Electrical system V 12

Fuel Consumption

 % 100 load lt/h 31,5

 % 75 load lt/h 24,1

 % 50 load lt/h 16,5

Lub.Oil Capacity lt 19

Coolant Capacity with radiator lt 37,2

ALTERNATOR

Manufacturer		MARELLI
Model		MJB250MA4
Stand By Power	kVA	180
Power Factor		0,8
Efficiency	%	92,9
Number of Bearing		Single
Leads Number		12
Voltage	V	230/400
Voltage Regulation Accuracy		±1%
Frequency	Hz	50
Insulation Class		H
Protection		IP23
Excitation System		Brushless, AVR
Connection		Star

All information given in this leaflet is intended for general purposes only. Due to a policy of continuous improvement, Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's cur